APPENDIX A			
CONTRACTOR SUBMITTAL TABLE			
ITEM	BRAND	MODEL/FEATURES	APPRX. QUANTITY
FLOOR COATING	UNSPECIFIED	Water-proof epoxy floor coat with non-slip surface.	210 SF
		Install per manufacturer's recommendations	
CMU WALL SEAL	UNSPECIFIED	Apply Sealant to existing CMU walls to prevent water	760 SF
		penetration and provide and easy to clean surface	
TOILET	ACORN	R2105-W-1 W/ HIDDEN FLUSH VALVE OPTION	4
SINK	DURA-WARE	1953-1-09-GT-H34	4
		Vandal resistant, stainless steel, wall mounted	
FAUCET	ZURN	WRB528143 Single Basin Metering Faucet	4
FLOOR DRAIN	UNSPECIFIED	4 inch minimum w/ metal grate	4
BREAKER PANEL	UNSPECIFIED	New 100 AMP breaker panel with a minimum of 20 spaces	1
INTERIOR LIGHT	KENALL	N1048 w/ motion activated timer and vandal resistant	4
		lens (timer should be independent from the exhaust fan)	
EXTERIOR LIGHT	KENALL	H1212ED Vandal resistant lens	4
EXHAUST FAN	UNSPECIFIED	100 CFM minimum, metal grill, motion sensor and	4
		timer (timer should be independent from the indoor	
		light)	
HAND DRYER	FASTAIRE	HDO3	4
SHOWER SEAT ADA	ASI	8208 all-stainless steel "L" shaped	2
SHOWER SEAT	ASI	8207 all-stainless steel	2
STANDARD			
SOAP DISPENSER	BOBRICK	B-8601	4
TOILET PAPER HOLDER	VANDAL STOP	AA-HRTD-LCx3E 12 gauge 316 Stainless	4
SANITARY WASTE RECEPTICAL	VANDAL STOP	VSP-SWR Stainless steel, vandal resistant, wall-mounted	4
EXTERIOR DOOR	UNSPECIFIED	36" steel commercial exterior solid core door. Install	4
EXTERIOR DOOR	UNSTECTIVED	vandal resistant, louvered vent.	7
DOOR CLOSER	BEST	HD8000 Heavy traffic use	4
DOOR KICKPLATE	UNSPECIFIED	Must meet code, 316 Stainless steel	4
GRAB BARS	UNSPECIFIED	Must meet code, 316 Stainless steel	12
WALL PENETRATIONS	N/A	Stamped approval from structural engineer specifying	N/A
WILLIENETRATION	14/21	temporary and permanent modifications required to complete the work.	14/11
FRAMING	N/A	Stamped approval from structural engineer specifying	N/A
CONNECTIONS	.,	connections	.,
BUILDING	N/A	Contractor to supply shop drawings or action plans for	N/A
RESTORATION AND		restoration from building modification. This shall	•
WATER PROOFING		include but is not limited to roof modifications, wall	
		modifications, flashing, and trim.	
ADA DIRECTIONAL	UNSPECIFIED	Wall sign with direction to the ADA bathrooms to be	2
SIGN		placed next to the Standard bathrooms	
BATHROOM SIGNS	UNSPECIFIED	Bathroom signs that clearly indicate that they are non-	4
		gendered bathrooms and if it is an ADA bathroom.	
WALL CLADDING	UNSPECIFIED	16 gauge 316 Stainless Steel wall cladding and mounting	510 SF
		materials. Finish shall be random swirl pattern	
WALL HOOKS	ASI AMERICAN SPECIALTIES	Stainless Steel breakaway hooks. Must break away at a minimum of 30 lbs. and a maximum of 40 lbs.	12
CRAWLSPACE HATCH	UNSPECIFIED	Lockable, paintable, and weather-proof access hatch.	2
CIVAMPOLACE HATCH	UNSPECIFIED	Lockable, paintable, and weather-proof access natch.	<u> </u>